

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** FB730PSB - AC730 PORTLAND STONE BASE

**Other means of identification:**

Not relevant

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses (Consumer use): Molding

Relevant uses (Professional users): Molding

Relevant uses (Industrial user): Molding

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

Jesmonite Limited

Challenge Court

SY95DW Bishops Castle - Shropshire - United Kingdom

Phone: +44 (0)1588 630302

www.Jesmonite.com

**1.4 Emergency telephone number:**

For advice on medical emergencies, fires, spillages or chemical hazards only phone: +44 1865 407333

## SECTION 2: HAZARDS IDENTIFICATION

**2.1 Classification of the substance or mixture:**

This product contains less than 1% respirable crystalline silica, so it does not require classification

**GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):**

Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).

Eye Dam. 1: Serious eye damage, Category 1, H318

Skin Sens. 1B: Sensitisation, skin, Category 1B, H317

**2.2 Label elements:**

**GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):**

**Danger**



**Hazard statements:**

Eye Dam. 1: H318 - Causes serious eye damage.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

**Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P261: Avoid breathing dust

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER/doctor.

P501: Dispose of the contents and/or its container using the separate collection system in your municipality.

**Supplementary information:**

Contains Flue dust, portland cement.

**Substances that contribute to the classification**

Cement, portland, chemicals (CAS: 65997-15-1)

**2.3 Other hazards:**

Product does not meet PBT/vPvB criteria

Date of compilation: 10/12/2025

Version: 1

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substance:

Not relevant

### 3.2 Mixture:

**Chemical description:** Mixture of cement, inorganic chemicals and additives

#### Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

| Identification                                                   | Chemical name/Classification                                                                                               | Concentration                                                                                                                                                                               |
|------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAS: 65997-16-2<br>EC: 266-045-5<br>REACH: 01-2119989490-26-XXXX | <b>Cement, alumina, chemicals</b><br>Eye Irrit. 2: H319 - Warning                                                          |  <b>30 - &lt;60%</b>                                                                                     |
| CAS: 65997-15-1<br>EC: 266-043-4                                 | <b>Cement, portland, chemicals</b><br>Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1B: H317; STOT SE 3: H335 - Danger |   <b>3 - &lt;5%</b>   |
| CAS: 68475-76-3<br>EC: 270-659-9<br>REACH: 01-2119486767-17-XXXX | <b>Flue dust, portland cement</b><br>Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Danger   |   <b>0.1 - &lt;1%</b> |

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

#### By skin contact:

May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters), seek medical advice with this Safety Data Sheet

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

### 4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media:

#### Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

#### Unsuitable extinguishing media:

Non-applicable

- CONTINUED ON NEXT PAGE -

## SECTION 5: FIREFIGHTING MEASURES (continued)

### 5.2 Special hazards arising from the substance or mixture:

The product is not flammable, it is not explosive, and does not enable or feed combustion in other materials

### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

#### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

#### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

### 6.4 Reference to other sections:

See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

#### A.- General precautions for safe use

Use in ventilated areas. Avoid the build up of dust

#### B.- Technical recommendations for the prevention of fires and explosions

Due to its non-flammable nature, the product does not present a fire risk under normal conditions of storage, handling and use.

#### C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

#### D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

### 7.2 Conditions for safe storage, including any incompatibilities:

#### A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 25 °C

Maximum time: 18 Months

#### B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5 Keep the container tightly sealed and protected from open air and humidity.

### 7.3 Specific end use(s):

## SECTION 7: HANDLING AND STORAGE (continued)

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

| Identification                                 | Occupational exposure limits |  |                      |
|------------------------------------------------|------------------------------|--|----------------------|
| Cement, portland, chemicals<br>CAS: 65997-15-1 | WEL (8h)                     |  | 4 mg/m <sup>3</sup>  |
|                                                | WEL (15 min)                 |  |                      |
| Aluminum Oxide<br>CAS: 1344-28-1               | WEL (8h)                     |  | 4 mg/m <sup>3</sup>  |
|                                                | WEL (15 min)                 |  |                      |
| Diiron trioxide<br>CAS: 1309-37-1              | WEL (8h)                     |  | 5 mg/m <sup>3</sup>  |
|                                                | WEL (15 min)                 |  | 10 mg/m <sup>3</sup> |

Nuisance dust: Inhalable dust 10 mg/m<sup>3</sup> // Respirable dust 4 mg/m<sup>3</sup>

#### DNEL (Workers):

| Identification                                                 |            | Short exposure      |                     | Long exposure         |                        |
|----------------------------------------------------------------|------------|---------------------|---------------------|-----------------------|------------------------|
|                                                                |            | Systemic            | Local               | Systemic              | Local                  |
| Cement, alumina, chemicals<br>CAS: 65997-16-2<br>EC: 266-045-5 | Oral       | Not relevant        | Not relevant        | Not relevant          | Not relevant           |
|                                                                | Dermal     | Not relevant        | Not relevant        | Not relevant          | Not relevant           |
|                                                                | Inhalation | 5 mg/m <sup>3</sup> | Not relevant        | 2.5 mg/m <sup>3</sup> | Not relevant           |
| Flue dust, portland cement<br>CAS: 68475-76-3<br>EC: 270-659-9 | Oral       | Not relevant        | Not relevant        | Not relevant          | Not relevant           |
|                                                                | Dermal     | Not relevant        | Not relevant        | Not relevant          | Not relevant           |
|                                                                | Inhalation | Not relevant        | 4 mg/m <sup>3</sup> | Not relevant          | 0.84 mg/m <sup>3</sup> |

#### DNEL (General population):

| Identification                                                 |            | Short exposure |              | Long exposure |                        |
|----------------------------------------------------------------|------------|----------------|--------------|---------------|------------------------|
|                                                                |            | Systemic       | Local        | Systemic      | Local                  |
| Flue dust, portland cement<br>CAS: 68475-76-3<br>EC: 270-659-9 | Oral       | Not relevant   | Not relevant | Not relevant  | Not relevant           |
|                                                                | Dermal     | Not relevant   | Not relevant | Not relevant  | Not relevant           |
|                                                                | Inhalation | Not relevant   | Not relevant | Not relevant  | 0.84 mg/m <sup>3</sup> |

#### PNEC:

| Identification                                                 |              |              |                         |              |
|----------------------------------------------------------------|--------------|--------------|-------------------------|--------------|
| Cement, alumina, chemicals<br>CAS: 65997-16-2<br>EC: 266-045-5 | STP          | 10 mg/L      | Fresh water             | 260 mg/L     |
|                                                                | Soil         | Not relevant | Marine water            | Not relevant |
|                                                                | Intermittent | 260 mg/L     | Sediment (Fresh water)  | Not relevant |
|                                                                | Oral         | Not relevant | Sediment (Marine water) | Not relevant |
| Flue dust, portland cement<br>CAS: 68475-76-3<br>EC: 270-659-9 | STP          | 6 mg/L       | Fresh water             | 0.282 mg/L   |
|                                                                | Soil         | 5 mg/kg      | Marine water            | 0.028 mg/L   |
|                                                                | Intermittent | 0.282 mg/L   | Sediment (Fresh water)  | 0.875 mg/kg  |
|                                                                | Oral         | Not relevant | Sediment (Marine water) | 0.088 mg/kg  |

### 8.2 Exposure controls:

#### A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### B.- Respiratory protection

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Pictogram                                                                                                                   | PPE                                                                 | Remarks                                                                                                                 |
|-----------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <br>Mandatory respiratory tract protection | Filter mask for gases, vapours and particles (Filter type: P2/FFP2) | Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected. |

### C.- Specific protection for the hands

| Pictogram                                                                                                      | PPE                                                                                              | Remarks                                          |
|----------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------|
| <br>Mandatory hand protection | Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.15 mm) | Replace the gloves at any sign of deterioration. |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

### D.- Eye and face protection

| Pictogram                                                                                                      | PPE                                           | Remarks                                                                                                                   |
|----------------------------------------------------------------------------------------------------------------|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| <br>Mandatory face protection | Panoramic glasses against splash/projections. | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

### E.- Body protection

| Pictogram | PPE                  | Remarks                                                                                                                                                                                                                                                           |
|-----------|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | Work clothing        | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994. |
|           | Anti-slip work shoes | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2022 y EN 13832-1:2019                                 |

### F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

| Emergency measure                                                                                       | Standards                                       | Emergency measure                                                                                        | Standards                                      |
|---------------------------------------------------------------------------------------------------------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------|------------------------------------------------|
| <br>Emergency shower | ANSI Z358-1<br>ISO 3864-1:2011, ISO 3864-4:2011 | <br>Eyewash stations | DIN 12 899<br>ISO 3864-1:2011, ISO 3864-4:2011 |

### Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

### The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

|                          |                 |
|--------------------------|-----------------|
| V.O.C. (Supply):         | 0 % weight      |
| V.O.C. density at 20 °C: | 0 kg/m³ (0 g/L) |

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

#### Appearance:

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

|                                              |                          |
|----------------------------------------------|--------------------------|
| Physical state at 20 °C:                     | Solid                    |
| Appearance:                                  | Powdery                  |
| Colour:                                      | Characteristic           |
| Odour:                                       | Odourless                |
| Odour threshold:                             | Not relevant *           |
| <b>Volatility:</b>                           |                          |
| Boiling point at atmospheric pressure:       | Not relevant *           |
| Vapour pressure at 20 °C:                    | Not relevant *           |
| Vapour pressure at 50 °C:                    | Not relevant *           |
| Evaporation rate at 20 °C:                   | Not relevant *           |
| <b>Product description:</b>                  |                          |
| Density at 20 °C:                            | 2839.9 kg/m <sup>3</sup> |
| Relative density at 20 °C:                   | 2.84                     |
| Dynamic viscosity at 20 °C:                  | Not relevant *           |
| Kinematic viscosity at 20 °C:                | Not relevant *           |
| Kinematic viscosity at 40 °C:                | Not relevant *           |
| Concentration:                               | Not relevant *           |
| pH:                                          | Not relevant *           |
| Vapour density at 20 °C:                     | Not relevant *           |
| Partition coefficient n-octanol/water 20 °C: | Not relevant *           |
| Solubility in water at 20 °C:                | Not relevant *           |
| Solubility properties:                       | Not relevant *           |
| Decomposition temperature:                   | Not relevant *           |
| Melting point/freezing point:                | Not relevant *           |
| <b>Flammability:</b>                         |                          |
| Flash Point:                                 | Not relevant *           |
| Flammability (solid, gas):                   | Not relevant *           |
| Autoignition temperature:                    | Not relevant *           |
| Lower flammability limit:                    | Not relevant *           |
| Upper flammability limit:                    | Not relevant *           |
| <b>Explosive (Solid):</b>                    |                          |
| Lower explosive limit:                       | Not relevant *           |
| Upper explosive limit:                       | Not relevant *           |
| <b>Particle characteristics:</b>             |                          |
| Median equivalent diameter:                  | Not relevant *           |

### 9.2 Other information:

#### Information with regard to physical hazard classes:

|                                                              |                |
|--------------------------------------------------------------|----------------|
| Explosive properties:                                        | Not relevant * |
| Oxidising properties:                                        | Not relevant * |
| Corrosive to metals:                                         | Not relevant * |
| Heat of combustion:                                          | Not relevant * |
| Aerosols-total percentage (by mass) of flammable components: | Not relevant * |

#### Other safety characteristics:

|                           |                |
|---------------------------|----------------|
| Surface tension at 20 °C: | Not relevant * |
|---------------------------|----------------|

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2025

Version: 1

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Refraction index:

Not relevant \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight       | Humidity            |
|--------------------|------------------|-------------------------|----------------|---------------------|
| Not applicable     | Not applicable   | Not applicable          | Not applicable | Avoid direct impact |

### 10.5 Incompatible materials:

| Acids        | Water                                    | Oxidising materials | Combustible materials | Others                                      |
|--------------|------------------------------------------|---------------------|-----------------------|---------------------------------------------|
| Incompatible | Silicate formation and calcium hydroxide | Not applicable      | Not applicable        | Base metal salts (Al, NH <sub>4</sub> ,...) |

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

#### A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

#### B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

#### C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces serious eye damage after contact.

#### D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- **Carcinogenicity:** Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
- IARC: Diiron trioxide (3)
- **Mutagenicity:** Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

### E- Sensitizing effects:

- **Respiratory:** Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- **Skin:** Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

### F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

### G- Specific target organ toxicity (STOT)-repeated exposure:

- **Specific target organ toxicity (STOT)-repeated exposure:** Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- **Skin:** Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

### H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

### Other information:

Contact with human skin, without adequate protection, can result in skin thickening, cracking, or fissuring

### Specific toxicology information on the substances:

| Identification                                                  | Acute toxicity       |             | Genus |
|-----------------------------------------------------------------|----------------------|-------------|-------|
| Cement, alumina, chemicals<br>CAS: 65997-16-2<br>EC: 266-045-5  | LD50 oral            | >2000 mg/kg |       |
|                                                                 | LD50 dermal          | >2000 mg/kg |       |
|                                                                 | LC50 inhalation dust | >5 mg/L     |       |
| Cement, portland, chemicals<br>CAS: 65997-15-1<br>EC: 266-043-4 | LD50 oral            | >2000 mg/kg |       |
|                                                                 | LD50 dermal          | >2000 mg/kg |       |
|                                                                 | LC50 inhalation dust | >5 mg/L     |       |
| Flue dust, portland cement<br>CAS: 68475-76-3<br>EC: 270-659-9  | LD50 oral            | >2000 mg/kg |       |
|                                                                 | LD50 dermal          | >2000 mg/kg |       |
|                                                                 | LC50 inhalation dust | >5 mg/L     |       |

## SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

### 12.1 Toxicity:

Not relevant

### 12.2 Persistence and degradability:

Not relevant

### 12.3 Bioaccumulative potential:

Not relevant

### 12.4 Mobility in soil:

Not relevant

### 12.5 Results of PBT and vPvB assessment:



Date of compilation: 10/12/2025

Version: 1

## SECTION 12: ECOLOGICAL INFORMATION (continued)

Product does not meet PBT/vPvB criteria

### 12.6 Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods:

| Code      | Description                                      | Waste class |
|-----------|--------------------------------------------------|-------------|
| 16 03 03* | inorganic wastes containing hazardous substances | Hazardous   |

Product - Cement that has exceeded its shelf life: 10 13 99

Product - Unused residue or dry spillage: 10 13 06

Product - after addition of water, hardened: 10 13 14, 17 01 01

#### Type of waste:

HP4 Irritant — skin irritation and eye damage

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

#### Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

## SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

#### The Control of Major Accident Hazards Regulations 2015:

Not relevant

#### Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc ....):

1. Cement and cement-containing mixtures shall not be placed on the market, or used, if they contain, when hydrated, more than 2 mg/kg (0,0002 %) soluble chromium VI of the total dry weight of the cement.
2. If reducing agents are used, then without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of cement or cement-containing mixtures is visibly, legibly and indelibly marked with information on the packing date, as well as on the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium VI below the limit indicated in paragraph 1.
3. By way of derogation, paragraphs 1 and 2 shall not apply to the placing on the market for, and use in, controlled closed and totally automated processes in which cement and cement-containing mixtures are handled solely by machines and in which there is no possibility of contact with the skin.  
Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

- CONTINUED ON NEXT PAGE -

## SECTION 15: REGULATORY INFORMATION (continued)

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

## SECTION 16: OTHER INFORMATION

### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

### Texts of the legislative phrases mentioned in section 2:

H318: Causes serious eye damage.

H317: May cause an allergic skin reaction.

### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

### Classification procedure:

Eye Dam. 1: Calculation method

Skin Sens. 1B: Calculation method

### Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

### Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer